




## DESCRIPTION

Angle Andy 25 was conceived as a multi-functional profile with a 45° asymmetric light distribution. Application possibilities include joinery such as under cabinet or retail displays, glass cabinets and jewellery displays, surface mounted wall washing, suspended wall washing and exterior applications when used with IP65 LED strip.

## FEATURES

- Made locally and factory assembled
- Unique mounting clip design for easy installation
- V-groove for accurate drilling and strip alignment
- Polycarbonate diffuser – UV resistant
- Max 20 W per metre

## TECHNICAL DATA

APPLICATIONS	Task lighting in kitchen cabinetry, lighting for shelving or display units, hallway lighting, wall-washing
INSTALLATION	Interior   Exterior (with IP65 LED strip)
MOUNTING	Surface mounted   Rod suspended
MATERIALS	Extruded aluminium body   Polycarbonate diffuser   AES plastic end caps
POWER SUPPLY	24V DC - remote driver options ranging from 6 W up to 320 W
DIMMABLE	DALI, 1-10V, Phase Cut and Bluetooth drivers available
WARRANTY	7 year product warranty   13 months labour warranty. Refer to <a href="http://www.lightculture.com.au">www.lightculture.com.au</a> for more details
LIGHT SOURCE	LED ribbon strip
SDCM*	2-step MacAdam
CRI*	≥ 95
R9*	80+
SOURCE LIFE*	L80 B10=82 000 hrs
FINISH	   Custom colours available

\* Figures for the PRO Series LED Strips



## LED STRIP

### PRO Series IP20 & IP65

6 W/m			12 W/m			18 W/m			30 W/m - IP20 only		
2700 K	3000 K	4000 K	2700 K	3000 K	4000 K	2700 K	3000 K	4000 K	2700 K	3000 K	4000 K
237 lm	237 lm	256 lm	493 lm	493 lm	529 lm	730 lm	776 lm	785 lm	-	-	-

### RGBW IP20 & IP65

22 W/m			
RED	GREEN	BLUE	3000K
47 lm	126 lm	31 lm	183 lm

The above outputs are quoting luminaire output lumens per metre  
 30 W/m strip only available in IP20.  
 IP65 strips are +/- 200 K in colour temperature variance due to the silicone coating.  
 Electrical and optical data variance +/- 10%

## ACCESSORIES



JMC-12  
Joinery mounting clip



JN-ST-12  
Straight joiner



JN-90-12  
90 degree joiner



JN-120-12  
120 degree joiner



JN-135-12  
135 degree joiner



SRK-1-S | SRK-1-W  
Rod suspension kit  
(Rod not included)



SRK-6-S | SRK-W  
Rod suspension kit  
(Rod not included)



ROD-0.5M | ROD-1M  
| ROD-2M  
Suspension rod -  
0.5m | 1m | 2m

